



Pneu-Dart X-Caliber Suggested Pressure Settings for 1/2cc – 10cc Dart Capacities

Distance	1/2 cc	1 cc	1 1/2 cc	2 cc	3 cc	4 cc	5 cc	6 cc	7 cc	8cc	10 cc
5 yds =	1.0 BAR	1.0 BAR	1.4 BAR	1.4 BAR	1.7 BAR	2.1 BAR	2.4 BAR	3.5 BAR	4.1 BAR	4.1 BAR	4.8 BAR
10 yds =	1.5 BAR	1.9 BAR	2.1 BAR	2.4 BAR	2.4 BAR	2.8 BAR	3.1 BAR	4.8 BAR	4.8 BAR	5.5 BAR	6.9 BAR
15 yds =	2.4 BAR	2.4 BAR	3.1 BAR	3.5 BAR	3.8 BAR	4.8 BAR	5.5 BAR	6.2 BAR	6.9 BAR	6.9 BAR	8.3 BAR
20 yds =	3.1 BAR	3.5 BAR	4.1 BAR	4.5 BAR	5.5 BAR	5.5 BAR	6.2 BAR	7.6 BAR	8.3 BAR	8.3 BAR	9.7 BAR
25 yds =	4.1 BAR	4.5 BAR	5.2 BAR	5.5 BAR	6.2 BAR	6.9 BAR	7.6 BAR	8.9 BAR	9.7 BAR	10.3 BAR	11.0 BAR
30 yds =	5.5 BAR	5.5 BAR	6.2 BAR	6.9 BAR	6.9 BAR	7.6 BAR	8.3 BAR	10.3 BAR	11.0 BAR	11.7 BAR	12.4 BAR
35 yds =	6.6 BAR	6.6 BAR	6.9 BAR	7.9 BAR	8.3 BAR	8.9 BAR	9.7 BAR	11.7 BAR	13.1 BAR	13.1 BAR	13.8 BAR
40 yds =	6.9 BAR	6.9 BAR	7.6 BAR	8.3 BAR	8.9 BAR	9.7 BAR	10.3 BAR	13.8 BAR	17.2 BAR	17.2 BAR	16.6 BAR
45 yds =	8.3 BAR	8.6 BAR	8.9 BAR	10.3 BAR	11.0 BAR	11.7 BAR	12.4 BAR	15.2 BAR	17.2 BAR	17.2 BAR	NR
50 yds =	8.6 BAR	9.0 BAR	11.7 BAR	NR	NR	NR	NR	NR	NR	NR	NR
55 yds =	10 BAR	10.3 BAR	NR	NR	NR	NR	NR	NR	NR	NR	NR
60 yds =	12.4 BAR	13.1 BAR	NR	NR	NR	NR	NR	NR	NR	NR	NR
65 yds =	13.8 BAR	14.5 BAR	NR	NR	NR	NR	NR	NR	NR	NR	NR
70 yds =	NR	NR	NR	NR	NR	NR	NR	NR	NR	NR	NR

• N/R = not recommended

Please note: This chart is a general guideline when using fully loaded Pneu Dart darts. Intended impact velocities may require alternate settings and/or altered points of aim.