



## Pneu-Dart X-2 Trajectory Table

Distance	1/2 cc	Reticle Position	1 cc	Reticle Position	1 1/2 cc	Reticle Position	2cc	Reticle Position
5 yds =	2.5 BAR	(+) 2"	3.0 BAR	(+) 1"	3.0 BAR	(+) 4"	3.0 BAR	(+) 1"
10 yds =	4.0 BAR	(-) 1"	4.0 BAR	(+) 1"	4.5 BAR	(+) 1"	5.0 BAR	0
15 yds =	5.0 BAR	0"	5.5 BAR	(+) 1"	6.5 BAR	(-) 3/4"	6.0 BAR	0
20 yds =	7.5 BAR	(+) 2"	7.5 BAR	(+) 4"	8.0 BAR	0	9.5 BAR	(+) 1"
25 yds =	9.0 BAR	(-) 2"	8.5 BAR	0"	10.0 BAR	0	N/R	N/R

- (+) implies hold above intended point of impact
- (-) implies hold below intended point of impact
- N/R = not recommended

**Please note: This chart is a general guideline when using fully loaded Pneu Dart darts. Intended impact velocities may require alternate settings and/or altered points of aim.**

BAR	PSI	BAR	PSI	BAR	PSI	BAR	PSI	BAR	PSI
4.1	60	5.2	75	6.2	90	7.6	110	9.7	140
4.5	65	5.5	80	6.6	95	8.3	120	10.3	150
4.8	70	5.9	85	6.9	100	9.0	130	11.7	170