

# Pneu-Dart X-2 Suggested Pressure Settings for 1/2cc – 2cc Dart Capacities

Distance	1/2 cc	Reticle Position	1 cc	Reticle Position	1 1/2 cc	Reticle Position	2cc	Reticle Position
5 yds =	2.5 BAR	(+) 2"	3.0 BAR	(+) 1"	3.0 BAR	(+) 4"	3.0 BAR	(+) 1"
10 yds =	4.0 BAR	(-) 1"	4.0 BAR	(+) 1"	4.5 BAR	(+) 1"	5.0 BAR	0
15 yds =	5.0 BAR	0"	5.5 BAR	(+) 1"	6.5 BAR	(-) 3/4"	6.0 BAR	0
20 yds =	7.5 BAR	(+) 2"	7.5 BAR	(+) 4"	8.0 BAR	0	9.5 BAR	(+) 1"
25 yds =	9.0 BAR	(-) 2"	8.5 BAR	0"	10.0 BAR	0	NR	NR

**Please note:** This chart is a general guideline when using fully loaded Pneu-Dart darts.  
Intended impact velocities may require alternate settings and/or altered points of aim.

(+) = implies hold above intended point of impact  
 (-) = implies hold below intended point of impact  
 NR = not recommended

BAR	PSI	BAR	PSI	BAR	PSI	BAR	PSI	BAR	PSI
4.1	60	5.2	75	6.2	90	7.6	110	9.7	140
4.5	65	5.5	80	6.6	95	8.3	120	10.3	150
4.8	70	5.9	85	6.9	100	9.0	130	11.7	170

